

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
23 December 2004 (23.12.2004)

PCT

(10) International Publication Number
WO 2004/111416 A1

(51) International Patent Classification⁷: **F02D 19/08**,
41/00, F02P 5/152

(21) International Application Number:
PCT/IB2004/001829

(22) International Filing Date: 4 June 2004 (04.06.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2003-167952 12 June 2003 (12.06.2003) JP

(71) Applicant (for all designated States except US): **TOYOTA JIDOSHA KABUSHIKI KAISHA** [JP/JP]; 1, Toyota-cho, Toyota-shi, Aichi-ken, 471-8571 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **ODA, Tomihisa** [JP/JP]; c/o Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi-ken 471-8571 (JP). **NIIMI, Kuniaki** [JP/JP]; Toyota Jidosha Kabushiki Kaisha, 1, Toyota-cho, Toyota-shi, Aichi-ken 471-8571 (JP).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SPARK IGNITION INTERNAL COMBUSTION ENGINE



(57) Abstract: A low-octane fuel and a high-octane fuel stored in a low-octane fuel tank (5) and a high-octane fuel tank (7), both having known octane numbers, are injected from fuel injection valves (13a, 13b) into an intake port (12) at a mixing proportion that achieves a standard octane number set in accordance with the engine operation state. If knocking occurs during a predetermined steady engine operation state, the knocking is detected by a knock sensor (10b) and, corresponding to the knocking, the ignition timing is retarded from a basic ignition timing. A deviation in octane number is determined from the amount of ignition timing retardation with reference to a map, and is then corrected by the intake air pressure. On the basis of the corrected deviation in octane number, a deviation in the mixing proportion of the high-octane fuel is determined with reference to a map. The thus-determined deviation is added to a target mixing proportion computed corresponding to the standard octane number, thereby computing the present mixing proportion.